

INSTALLATION INSTRUCTIONS

Model # 9306

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

PREPARING FOR INSTALLATION (Fig. 1)

1. Shut off power at the circuit breaker (avertissement! couper le courant au niveau des fusibles ou du disjoncteur) and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts in a clear area. Take care not to misplace any small parts necessary for installation.

CONNECTING THE WIRES (Fig. 2)

3. While supporting the fixture, connect the electrical wires while supporting the lantern. If your post has a ground wire (green or bare copper), connect the fixture ground wire to it. If not, consult your electrician for proper grounding. After wires are connected, tuck them carefully inside the post cup (I).

COMPLETING THE INSTALLATION (Fig. 1)

4. Align the lantern with post (K) and secure with screws (J) (**Part#8/32"×3/8"L**). (Fig.1)
5. At this point, put the glass shade in metal ring (D) and then install the glass shade. Align bulb holder (G) over the nipple and secure with ring (F),
6. Install 1*100W A bulb in accordance with the fixture specification -----**DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NOTE: NO BULB INCLUDED)(NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**
7. Align the top cover (A) onto the glass shade and secure the metal ring (D) to the top cover (A) with screws (E).

Your installation is now complete. Return power to the outlet box and test the fixture.

IMPORTANT: FIXTURE SHOULD BE INSTALLED BY A QUALIFIED ELECTRICIAN TO ENSURE PROPER WIRING AND INSTALLATION.

Fig. 1

